

# Cisco 2-Port OC-3/STM-1 Packet-over-SONET Port Adapter

To meet the continual need for increased router features and performance, Cisco Systems® introduces its newest packet-over-SONET (POS) port adapter, the Cisco® 2-Port OC-3/STM-1 POS Port Adapter. The 2-Port OC-3/STM-1 POS Port Adapter is ideal for service providers or large enterprises that need to deploy multiple ports of OC-3/STM-1 connectivity or a single OC-3/STM-1 port with redundancy and failover support.

The 2-Port OC-3/STM-1 POS Port Adapter (Figure 1) combines superior performance and an innovative design to provide the following benefits:

- Σ Dual-port, line-rate performance
- Σ Automatic protection switching (APS) failover between ports
- Σ Modular, pluggable optics (Three types are available: multimode fiber, short range [MM]; single-mode fiber, intermediate range [SMIR]; and single-mode fiber, long range [SMLR])

**Figure 1**  
Cisco 2-Port OC-3/STM-1 POS Port Adapter



## Features and Benefits

Table 1 describes the features and benefits of the Cisco 2-Port OC-3/STM-1 POS Port Adapter.

**Table 1.** Features and Benefits of the Cisco 2-Port OC-3/STM-1 POS Port Adapter

Features	Benefits
<b>Dual port connectivity</b>	Greater per-slot density for Cisco platforms using port adapter technology (for example, on the Cisco 7200 or Cisco 7400 Series)
<b>Performance</b>	Depending on processing engine, provides line-rate bidirectional performance across both ports*
<b>APS</b>	Provides failover protection between POS ports and/or port adapters
<b>Modular Small Form-Factor Pluggable (SFP) optics</b>	Greater flexibility in deployment and sparing; allows for mixed optics on a single port adapter


\* Performance constrained only by processing engine

## Modular Optics

The 2-Port OC-3/STM-1 POS Port Adapter offers support for two modular SFP optics. Figure 2 illustrates these ports.

**Figure 2**

Cisco 2-Port OC-3/STM-1 POS Port Adapter Modular Optics



## SFP Optics

The 2-Port OC-3/STM-1 POS Port Adapter supports two ports of any of the following SFP optics: multimode (MM), single-mode fiber intermediate range (IR), and single-mode fiber long range (LR). Two different module types may be mixed in the same port adapter. The Product Ordering section of this document provides product part numbers for the SFPs used with the 2-Port OC-3/STM-1 POS Port Adapter.

## Product Specifications

### Chassis and Processors

The Cisco 2-Port OC-3/STM-1 POS Port Adapter is supported on the platforms and processors indicated in Table 2.

**Table 2.** Chassis and Processor Compatibility

Chassis	Processors
Cisco 7204VXR, 7206VXR, 7301	NPE-G1, NPE-400, NSE-1
Cisco 7304	NSE-100 and NPE-G100
Cisco 7505, 7507, 7513	VIP6-80, VIP4-80; RSP 16, RSP 8
Cisco 7600	FlexWan and the Enhanced FlexWan

### Port Adapters

The 2-Port OC-3/STM-1 POS Port Adapter interoperates with all port adapters that are available for order (as of January 2003) with the Cisco 7200VXR, 7301, 7304, 7500, and 7600 routers.

## Software

The 2-Port OC-3/STM-1 POS Port Adapter is supported in Cisco IOS® Software Release 12.2(13)ZE, 12.3, 12.3T, 12.2S(RLS3), 12.0(27)S, and later. Consult your Cisco representative for more details.

## Key Features

The primary features of the 2-Port OC-3/STM-1 POS Port Adapter are described in this section.

### Hardware and Software Features

- Σ Single-wide port adapter form factor
- Σ Two concatenated OC-3/STM-1 ports
- Σ Line-rate performance
- Σ Online insertion and removal (OIR)
- Σ Modular optics supporting single mode (intermediate and long reach) and multimode

## Product Specifications

### Physical

- Σ Weight: Approximately 14 oz
- Σ Dimensions (H x W x D): Approximately 1 in. x 6 5/8 in. x 5 \_ in. (body only)
- Σ Approximately 1 in. x 6 5/8 in. x 7 in. (overall)

### Environmental

- Σ Storage temperature: –38 to 150°F (–40 to 70°C)
- Σ Operating temperature, nominal: 25°C (ranges 0–40°C)
- Σ Operating temperature, short term: 23 to 131°F (–5 to 55°C)
- Σ Storage relative humidity: 5 to 95% relative humidity (RH)
- Σ Operating humidity, nominal: 5 to 85% RH
- Σ Operating humidity, short term: 5 to 90% RH
- Σ Operating altitude: –60 to 2000 m

### Regulatory Compliance

CE Marking

### Safety

UL 60950

IEC 60950

EN 60950

CAN/CSA-C22.2 No. 60950

AS/NZS 3260

## EMC

FCC Part 15 (CFR 47) Class A

ICES-003 Class A

EN55022 Class A

CISPR22 Class A

AS/NZS 3548 Class A

VCCI Class A

EN55024

ETS300 386

EN50082-1

EN61000-3-2

EN61000-3-3

EN61000-6-1

## Product Ordering Details

Please visit: <https://www.cisco.com/c/en/us/services/order-services.html> to place an order using the information in Tables 3 and 4.

**Table 3.** Port Adapter Ordering Information

Product Number	Product Description
PA-POS-2OC3	Cisco 2-Port OC-3/STM-1 POS Port Adapter
PA-POS-2OC3=	Cisco 2-Port OC-3/STM-1 POS Port Adapter (Spare)

**Table 4.** SFP Ordering Information

Product Number	Product Description
SFP-OC3-MM	OC-3/STM-1 POS SFP, multimode fiber, short range (MM)
SFP-OC3-IR1	OC-3/STM-1 POS SFP, single-mode fiber, intermediate range (SMI)
SFP-OC3-LR1	OC-3/STM-1 POS SFP, single-mode fiber, long range (SML)

## Service and Support

Cisco Systems offers a wide range of service and support options for its customers. More information about Cisco service and support programs and benefits can be found at: <http://www.cisco.com/en/us/support>.



**Corporate Headquarters**

Cisco Systems, Inc.  
170 West Tasman Drive  
San Jose, CA 95134-1706  
USA  
www.cisco.com  
Tel: 408 526-4000  
800 553-NETS (6387)  
Fax: 408 526-4100

**European Headquarters**

Cisco Systems International BV  
Haarlerbergpark  
Haarlerbergweg 13-19  
1101 CH Amsterdam  
The Netherlands  
www-europe.cisco.com  
Tel: 31 0 20 357 1000  
Fax: 31 0 20 357 1100

**Americas Headquarters**

Cisco Systems, Inc.  
170 West Tasman Drive  
San Jose, CA 95134-1706  
USA  
www.cisco.com  
Tel: 408 526-7660  
Fax: 408 527-0883

**Asia Pacific Headquarters**

Cisco Systems, Inc.  
168 Robinson Road  
#28-01 Capital Tower  
Singapore 068912  
www.cisco.com  
Tel: +65 6317 7777  
Fax: +65 6317 7799

Cisco Systems has more than 200 offices in the following countries and regions. Addresses, phone numbers, and fax numbers are listed on the **Cisco Website at [www.cisco.com/go/offices](http://www.cisco.com/go/offices).**

Argentina • Australia • Austria • Belgium • Brazil • Bulgaria • Canada • Chile • China PRC • Colombia • Costa Rica  
Croatia • Cyprus • Czech Republic • Denmark • Dubai, UAE • Finland • France • Germany • Greece • Hong Kong SAR  
Hungary • India • Indonesia • Ireland • Israel • Italy • Japan • Korea • Luxembourg • Malaysia • Mexico  
The Netherlands • New Zealand • Norway • Peru • Philippines • Poland • Portugal • Puerto Rico • Romania • Russia  
Saudi Arabia • Scotland • Singapore • Slovakia • Slovenia • South Africa • Spain • Sweden • Switzerland • Taiwan  
Thailand • Turkey • Ukraine • United Kingdom • United States • Venezuela • Vietnam • Zimbabwe

All contents are Copyright © 1992–2005 Cisco Systems, Inc. All rights reserved. Cisco, Cisco IOS, Cisco Systems, and the Cisco Systems logo are registered trademarks or trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0502R)

Pa/LW8976 07/05