

Cisco CRS 8-Port 10 Gigabit Ethernet Interface Module

The Cisco® CRS-1 Carrier Routing System is the industry's first carrier router offering continuous system operation, unprecedented service flexibility, and system longevity. The Cisco CRS-1 is powered by Cisco IOS® XR Software – a unique self-healing, distributed operating system designed for always-on operation while scaling system capacity up to 92 Tbps. The innovative system architecture combines the Cisco Silicon Packet Processor, the first programmable 40-Gbps application-specific integrated circuit (ASIC), with the Cisco Service Separation Architecture for unprecedented service flexibility and speed to service. The Cisco CRS-1 marks a new era in carrier IP Communications by powering the foundation for network and service convergence today while protecting investments for decades to come.

This data sheet provides detailed product specifications for the Cisco CRS-1 8-Port 10 Gigabit Ethernet Interface Module. For more information about the Cisco CRS-1 or about other interfaces available for the Cisco CRS-1, visit: <http://www.cisco.com/go/crs>.

Figure 1. Cisco CRS-1 8-Port 10 Gigabit Ethernet Interface Module



Product Specifications

Table 1. Product Specifications

Feature	Description
Chassis Compatibility	Compatible with all current Cisco CRS-1 and CRS-3 line-card chassis
Software Compatibility	Cisco IOS XR Software Release 3.0 or later for CRS-1 Cisco IOS XR Software Release 4.0.0 or later for CRS-3
Port Density	Eight ports of 10 Gigabit Ethernet per PLIM slot
Ethernet	Encapsulations: ARPA, IEEE 802.2/SAP, IEEE 802.3/SNAP IEEE 802.x flow control 802.1q VLAN support, jumbo frames IEEE 802.1p tagging Source/destination MAC accounting and VLAN accounting
Reliability and Availability	Online insertion and removal (OIR) without affecting system traffic

Feature	Description
Network Management	Cisco IOS XR Software command-line interface (CLI) Simple Network Management Protocol (SNMP) Extensible Markup Language (XML) interface CraftWorks Interface (CWI)
Physical Dimensions	Occupies one PLIM slot Weight: 8.4 lb (3.8 kg) Height: 20.6 in. (52.2 cm) Depth: 11.2 in. (28.4 cm) Width: 1.8 in. (4.49 cm)
Power	150W
Environmental Conditions	Storage Temperature: –40 to 70°C (–40 to 158°F) Operating Temperature: Normal: 5 to 40°C (41 to 104°F) Short-term: –5 to 50°C (23 to 122°F) short-term Relative Humidity: Normal: 5% to 85% Short-term: 5% to 90% but not to exceed 0.024 kg water/kg of dry air Short-term refers to a period of not more than 96 consecutive hours and a total of not more than 15 days in 1 year. (This refers to a total of 360 hours in any given year, but no more than 15 occurrences during that 1-year period.)

Approvals and Compliance

Table 2. Compliance and Agency Approvals

Feature	Description
Safety Standards	UL/CSA/IEC/EN 60950-1 IEC/EN 60825 Laser Safety ACA TS001 AS/NZS 60950 FDA – Code of Federal Regulations Laser Safety
EMI	FCC Class A ICES 003 Class A AS/NZS 3548 Class A CISPR 22 (EN55022) Class A VCCI Class A BSMI Class A IEC/EN 61000-3-2: Power Line Harmonics IEC/EN 61000-3-3: Voltage Fluctuations and Flicker
Immunity (Basic Standards)	IEC/EN-61000-4-2: Electrostatic Discharge Immunity (8 kV Contact, 15 kV Air) IEC/EN-61000-4-3: Radiated Immunity (10 V/m) IEC/EN-61000-4-4: Electrical Fast Transient Immunity (2 kV Power, 1 kV Signal) IEC/EN-61000-4-5: Surge AC Port (4 kV CM, 2 kV DM) IEC/EN-61000-4-5: Signal Ports (1 kV) IEC/EN-61000-4-5: Surge DC Port (1 kV) IEC/EN-61000-4-6: Immunity to Conducted Disturbances (10 Vrms) IEC/EN-61000-4-8: Power Frequency Magnetic Field Immunity (30 A/m) IEC/EN-61000-4-11: Voltage DIPS, Short Interruptions, and Voltage Variations
ETSI and EN	EN300 386: Telecommunications Network Equipment (EMC) EN55022: Information Technology Equipment (Emissions) EN55024: Information Technology Equipment (Immunity) EN50082-1/EN-61000-6-1: Generic Immunity Standard
Network Equipment Building Systems (NEBS)	This product is designed to meet the following requirements (qualification in progress): SR-3580: NEBS Criteria Levels (Level 3) GR-1089-CORE: NEBS EMC and Safety GR-63-CORE: NEBS Physical Protection

Additional Specifications

Table 3. Additional Specifications

Parameter	Long Reach 1310 nm (LR/LR+)	Extended Reach 1550 nm (ER+)	DWDM 1530.33-1560.61 nm
Connector Type	SC	SC	SC
Target Distance	10 km	40 km	80 km
Transmitter			
Power out (maximum)	0.5 dBm	4 dBm	3 dBm
Power out (minimum)	-8.2 dBm	-4.7 dBm	-1.0 dBm
Receiver			
P (RMax) (overload)	0.5 dBm	-1.0 dBm	-7.0 dBm
P (RMin) (sensitivity)	-14.4 dBm	-15.8 dBm	-24.0 dBm
Optical Link			
Fiber type	G.652 (single-mode fiber [SMF])	G.652 (SMF)	G.652 (SMF)
Optical path penalty	3.2 dB	4.1 dB	3.0 dB
Compliance	IEEE 802.3ae 10GBASE-LR	IEEE 802.3ae 10GBASE-ER	IEEE 802.3ae 10GBASE

Ordering Information

To place an order, visit: [Cisco Ordering Home Page](#).

Table 4. Ordering Information

Product Part Number	Product Name
8-10GBE(=)	Cisco CRS-1 Carrier Routing System 8-port 10 Gigabit Ethernet Interface Card
CRS-XENPAK-10GB-LR(=)	XENPAK 10GBASE-LR Optics Module
XENPAK-10GB-LR+(=)	XENPAK 10GBASE-LR+ Optics Module
XENPAK-10GB-ER+(=)	XENPAK 10GBASE-ER+ Optics Module
DWDM-XENPAK-60.61= to DWDM-XENPAK-30.33=	XENPAK 10GBASE DWDM Modules (32 ITU 100-GHz wavelengths)

Service and Support

Cisco offers numerous innovative services programs to accelerate customer success. These programs are delivered through a unique combination of people, processes, tools, and partners, resulting in high levels of customer satisfaction. Cisco services help you to protect your network investment, optimize network operations, and prepare the network for new applications to extend network intelligence and the power of your business. For more information about Cisco services, see [Cisco Technical Support Services](#) or [Cisco Advanced Services](#).

For More Information

For more information about the Cisco CRS-1 8-Port 10 Gigabit Ethernet Interface Module, contact your local account representative or visit: <http://www.cisco.com/go/crs>.



Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV
Amsterdam, The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

CCDE, CCENT, CCSI, Cisco Eos, Cisco Explorer, Cisco HealthPresence, Cisco IronPort, the Cisco logo, Cisco Nurse Connect, Cisco Pulse, Cisco SensorBase, Cisco StackPower, Cisco StadiumVision, Cisco TelePresence, Cisco TrustSec, Cisco Unified Computing System, Cisco WebEx, DCE, Flip Channels, Flip for Good, Flip Mino, Flipshare (Design), Flip Ultra, Flip Video, Flip Video (Design), Instant Broadband, and Welcome to the Human Network are trademarks; Changing the Way We Work, Live, Play, and Learn, Cisco Capital, Cisco Capital (Design), Cisco:Financed (Stylized), Cisco Store, Flip Gift Card, and One Million Acts of Green are service marks; and Access Registrar, Aironet, AllTouch, AsyncOS, Bringing the Meeting To You, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, CCVP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Lumin, Cisco Nexus, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Collaboration Without Limitation, Continuum, EtherFast, EtherSwitch, Event Center, Explorer, Follow Me Browsing, GainMaker, iLYNX, IOS, iPhone, IronPort, the IronPort logo, Laser Link, LightStream, Linksys, MeetingPlace, MeetingPlace Chime Sound, MGX, Networkers, Networking Academy, PCNow, PIX, PowerKEY, PowerPanels, PowerTV, PowerTV (Design), PowerVu, Prisma, ProConnect, ROSA, SenderBase, SMARTnet, Spectrum Expert, StackWise, WebEx, and the WebEx logo are registered trademarks of Cisco and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1002R)