

Cisco CRS 8-Slot Line-Card Chassis Route Processor

The Cisco® CRS-1 Carrier Routing System is the industry’s first carrier router offering continuous system operation, unprecedented service flexibility, and system longevity. The Cisco CRS-1 is powered by Cisco IOS® XR Software – a unique self-healing, distributed operating system designed for always-on operation while scaling system capacity up to 92 Tbps. The innovative system architecture combines the Cisco Silicon Packet Processor, the first programmable 40-Gbps application-specific integrated circuit (ASIC), with the Cisco Service Separation Architecture for unprecedented service flexibility and speed to service. The Cisco CRS-1 marks a new era in carrier IP Communications by powering the foundation for network and service convergence today while protecting investments for decades to come.



This data sheet provides detailed product specifications for the Cisco CRS-1 8-Slot Line-Card Chassis Route Processor. For more information about the Cisco CRS-1 or other interfaces available on the Cisco CRS-1, visit: <http://www.cisco.com/go/crs>.

Product Specifications

Table 1. Specifications of Cisco CRS-1 8-Slot Line-Card Chassis Route Processor.

Feature	Description
Chassis Compatibility	Compatible with the Cisco CRS-1 and CRS-3 8-Slot Line-Card Chassis
Software Compatibility	Cisco IOS XR Software Release 3.00 or higher for CRS-1 Cisco IOS XR Software Release 4.0.0 or later for CRS-3
Protocols	Cisco Discovery Protocol IPv4 and IPv6 addressing Internet Control Message Protocol (ICMP) Layer 3 routing protocols, including Border Gateway Protocol Version 4 (BGPv4), Open Shortest Path First Version 2 (OSPFv2), OSPFv3, Intermediate System-to-Intermediate System Protocol (IS-IS) Multicast forwarding with support for source-based and shared distribution trees and the following protocols: <ul style="list-style-type: none"> • Protocol Independent Multicast sparse mode (PIM-SM) • Bi-directional PIM (Bidir-PIM) • PIM Source Specific Multicast (PIM SSM) • Automatic route processing (AutoRP)

Feature	Description
	<ul style="list-style-type: none"> • Internet Group Management Protocol (IGMP) versions 1,2 and 3 • Multiprotocol BGP (MBGP) • Multicast Source Discovery Protocol (MSDP) Multiprotocol Label Switching (MPLS) <ul style="list-style-type: none"> • MPLS Label Distribution Protocol (LDP) • Resource Reservation Protocol (RSVP) • Diffserv Aware TE MPLS Traffic Engineering control plane (RFCs 2702 and 2430) Route Policy Language (RPL) Management: <ul style="list-style-type: none"> • Simple Network Management Protocol (SNMP) • Programmatic interfaces (XML) Security: <ul style="list-style-type: none"> • Message Digest Algorithm (MD5) • IP Security (IPSec) Protocol • Secure Shell (SSHv2) • Secure FTP (SFTP) • Secure Sockets Layer (SSL)
Connectivity	<ul style="list-style-type: none"> • Console port (RJ-45 connector) • Auxiliary port (RJ-45 connector) • One 10/100/1000 Ethernet port (RJ-45 connector) • Two 10/100/1000 Ethernet ports (1000BASE-LX Small Form-Factor Pluggable (SFP)-LC connector, 10 km) for control-plane connectivity
Memory	<ul style="list-style-type: none"> • 4 GB of route memory • 64 MB of boot Flash memory • 2 MB of NVRAM • One 1-GB PCMCIA card (internal) • One 40-GB hard drive
Options	<ul style="list-style-type: none"> • 4 GB of route memory (two 2-GB modules) • One 1-GB PCMCIA card
Performance	One 1.2-GHz Power PC
Reliability and Availability	Software Features: <ul style="list-style-type: none"> • Cisco Nonstop Forwarding (NSF) • Hot Standby Router Protocol (HSRP) and Virtual Router Redundancy Protocol (VRRP) • Online insertion and removal (OIR) • MPLS Fast Reroute (FRR)
MIBs	SNMP Framework Support: <ul style="list-style-type: none"> • SNMPv1 • SNMPv2c • SNMPv3 • MIB II, including interface extensions (RFC 1213) • SNMP-FRAMEWORK-MIB • SNMP-TARGET-MIB • SNMP-NOTIFICATION-MIB • SNMP-USM-MIB • SNMP-VACM-MIB System Management: <ul style="list-style-type: none"> • CISCO- BULK-FILE-MIB • CISCO-CONFIG-COPY-MIB • CISCO-CONFIG-MAN-MIB • CISCO-FLASH-MIB • CISCO-MEMORY-POOL-MIB • Cisco FTP Client MIB • Cisco Process MIB

Feature	Description
	<ul style="list-style-type: none"> • Cisco Syslog MIB • CISCO-SYSTEM-MIB • CISCO-CDP-MIB • IF-MIB (RFC 2233/RFC 2863) <p>Chassis:</p> <ul style="list-style-type: none"> • ENTITY-MIB (RFC 2737) • CISCO-entity-asset-MIB • CISCO-entity-sensor-MIB • CISCO-FRU-MIB (Cisco-Entity-FRU-Control-MIB) <p>Fabric:</p> <ul style="list-style-type: none"> • CISCO-Fabric-HFR-MIB • CISCO-Fabric-Mcast-MIB • CISCO-Fabric-Mcast-Appl-MIB <p>Routing Protocols:</p> <ul style="list-style-type: none"> • BGP4-MIB Version 1 • OSPFv1-MIB (RFC 1253) • CISCO-IETF-IP-FORWARDING-MIB • IP-MIB (was RFC 2011-MIB) • TCP-MIB (RFC 2012) • UDP-MIB • CISCO-HSRP-EXT-MIB • CISCO-HSRP-MIB • CISCO-BGP-POLICU-ACCOUNTING-MIB <p>Quality of Service (QoS):</p> <ul style="list-style-type: none"> • MQC-MIB (Cisco Class-Based QoS MIB) • CISCO-PING-MIB <p>MPLS:</p> <ul style="list-style-type: none"> • MPLS-LDP-MIB • MPLS-LSR-MIB • MPLS-TE-MIB <p>Traps:</p> <ul style="list-style-type: none"> • RFC 1157 • Authentication • Linkup • Linkdown • Coldstart • Warmstart
Network Management	<ul style="list-style-type: none"> • Enhanced command-line interface (CLI) • Extensible Markup Language (XML) interface • XML schemas • Craft Works Interface (CWI) • SNMP and MIB support
Programmatic interfaces	XML Schema support
Physical Dimensions	<ul style="list-style-type: none"> • Weight: 8.75 lb (3.96 kg) • Height: 20.6 in. (52.2 cm) • Width: 1.3875. (3.524 cm) • Depth: 11.2 in. (28.4 cm)
Power	96W

Approvals and Compliance

Table 2. Compliance and Agency Approvals

Feature/Agency	Description
Safety Standards	<ul style="list-style-type: none"> • UL/CSA/IEC/EN 60950-1 • IEC/EN 60825 laser safety • ACA TS001 • AS/NZS 60950 • FDA – Code of Federal Regulations laser safety
EMI	<ul style="list-style-type: none"> • FCC Class A • ICES 003 Class A • AS/NZS 3548 Class A • CISPR 22 (EN55022) Class A • VCCI Class A • BSMI Class A • IEC/EN 61000-3-2: Power Line Harmonics • IEC/EN 61000-3-3: Voltage Fluctuations and Flicker
Immunity (Basic Standards)	<ul style="list-style-type: none"> • IEC/EN-61000-4-2: Electrostatic Discharge Immunity (8-kV Contact, 15-kV Air) • IEC/EN-61000-4-3: Radiated Immunity (10 V/m) • IEC/EN-61000-4-4: Electrical Fast Transient Immunity (2-kV Power, 1-kV Signal) • IEC/EN-61000-4-5: Surge AC Port (4-kV CM, 2-kV DM) • IEC/EN-61000-4-5: Signal Ports (1 kV) • IEC/EN-61000-4-5: Surge DC Port (1 kV) • IEC/EN-61000-4-6: Immunity to Conducted Disturbances (10 Vrms) • IEC/EN-61000-4-8: Power Frequency Magnetic Field Immunity (30A/m) • IEC/EN-61000-4-11: Voltage DIPS, Short Interruptions, and Voltage Variations
ETSI and EN	<ul style="list-style-type: none"> • EN300 386: Telecommunications Network Equipment (EMC) • EN55022: Information Technology Equipment (Emissions) • EN55024: Information Technology Equipment (Immunity) • EN50082-1/EN-61000-6-1: Generic Immunity Standard
Network Equipment Building Standards (NEBS)	<p>This product is designed to meet the following requirements (qualification in progress):</p> <ul style="list-style-type: none"> • SR-3580: NEBS Criteria Levels (Level 3) • GR-1089-CORE: NEBS EMC and Safety • GR-63-CORE: NEBS Physical Protection

Ordering Information

To place an order (refer to Table 3), visit: [Cisco Ordering Home Page](#).

Table 3. Ordering Information

Product Part Number	Product Name
GLC-LH-SM(=)	Cisco Gigabit Ethernet SFP LC connector LX/LH transceiver; GLC-LH-SM
GLC-LH-SMD(=)	Cisco Gigabit Ethernet SFP LC connector LX/LH transceiver; with DOM
CRS-8-RP(=)	Cisco CRS-1 8-Slot Line-Card Chassis Route Processor
CRS-8-RP/R	Cisco CRS-1 8 Slot Line Card Chassis Redundant Route Processor

End-of-Sale and End-of-Life Announcement for the Select Cisco Gigabit Ethernet SFP Modules:

http://www.cisco.com/en/US/prod/collateral/modules/ps5455/eol_c51-698060.html

To download Cisco IOS® Software, visit: [Cisco Software Center](#).

Service and Support

Cisco Systems® offers numerous innovative services programs to accelerate customer success. These programs are delivered through a unique combination of people, processes, tools, and partners, resulting in high levels of customer satisfaction. Cisco services help you protect your network investment, optimize network operations, and prepare your network for new applications to extend network intelligence and the power of your business. For more information about Cisco services, visit: [Cisco Technical Support Services](#) or [Cisco Advanced Services](#).

For More Information

For more information about the 8-slot route processor for the Cisco CRS-1, contact your local Cisco account representative or visit Cisco at: <http://www.cisco.com/go/crs>.



Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)